

# EPA Wood Burning Fireplaces

Timeless Beauty





## Stratton Wood Burning Fireplace

This small, EPA wood burning fireplace is perfect for any room requiring both warmth and style. Able to hold logs between 18 and 20 inches and offering 10,100 to 27,550 BTUs per hour, the Stratton easily heats up to 1500 square feet. With its large viewing window, traditional Black finish and cast iron construction, the Stratton will provide durability and beauty for years to come.

Stratton with Circa front Black Texture Face kit shown on cover



## Sequoia Wood Burning Fireplace

The heat generated by a Vermont Castings<sup>®</sup> remarkable Sequoia EPA wood burning fireplace is just the beginning. Meeting Washington state emissions standards, EPA Phase II certified and featuring clean-burn technology, the catalytic Sequoia can heat up to 2,500 square feet of your home as efficiently as a wood stove. It's a new tradition in fireplace design and it's only available from Vermont Castings.



### Comfort & Style

Cast in tradition and manufactured with the fine craftsmanship and attention to detail that heritage brings, a Vermont Castings stove or fireplace offers classic warmth and timeless beauty that stands out from the competition. Light the fire of comfort and style in your home and add the perfect gathering place. Add a Vermont Castings.



## Built Vermont Proud and Strong



#### **EPA Wood Burning Fireplaces**

Model	Stratton	Sequoia EWF36
Max BTUs	40,000	
Thermal Efficiency	68%	73%
Dimensions (Actual)	35.25"W x 36.16"H x 22.21"D	43″W x 51.5″H x 27″D
Dimensions (Framing)	36.5"W x 36.5"H x 23"D	43″W x 51.5″H x 27″D
Viewing Area	280 sq.in	36″W x 20.25 H
Area Heated	up to 1,500 sq. ft.	up to 2,500 sq. ft.
Minimum Fireplace Dimensions	18" (Rear Width) x 21.5" (Front Width) x 14.75" D x 10.75" H	
Firebox Size (cubic ft.)	2.1	4.2
Emission (Grams/hr)	3	2.5
Radiant or Circulating		Radiant + Circulating
Design Certified	OMNI	UL / ULC

<ul><li>Stratton Features &amp; Benefits</li><li>Burn rate: 10,100 - 27,550 BTUs/hr.</li><li>EPA Emissions Rating : 3.0g./hr.</li></ul>	<ul> <li>Cast Iron Construction</li> <li>Fits log length 18" to 20"</li> <li>Removable internal baffle.</li> </ul>	<ul> <li>Uses SK8 chimney or triple wall pipe with TWABR adapter</li> <li>Large viewing area</li> </ul>
<ul><li>Optional Accessories</li><li>Heat Activated Fan Kit</li></ul>	Face Kit (Required) <ul> <li>Stratton Circa Front Black Texture</li> </ul>	
Sequoia Features & Benefits	• Arched cast iron doors are air sealed	Uses Majestic triple wall chimney system
<ul> <li>Heat output: 11,300 to 75,500 BTU/hr (based on EPA ratings)</li> <li>Less than 2.5 g/hr particulate emissions</li> <li>Ceramic glass window features glass air-wash system</li> </ul>	<ul> <li>Burn time up to 14 hours</li> <li>Size of logs up to 24"</li> <li>Large ash handling system with two removable ash pans</li> </ul>	<ul> <li>Twin outside air kit (AK-MST)</li> <li>Weight: 741lbs</li> </ul>
Optional Accessories	Face Kits (One Required)	

- FK26 fan
- EWF36S spark screen

• EWF36CFTK cast iron face kit

- EWF36CLK latticed cast iron grills
- For more information about MHSC and Vermont Castings efficient and environmentally friendly products, please visit www.vermontcastings.com



To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2010 Monessen Hearth Systems Co.